

Specifications are subject to change without notice.

| ITEM                            | SPECIFICATION  |
|---------------------------------|--|
| Dimensions                      | 17.1" W x 21.5" D x 15.3" H (435 x 547 x 389 mm)<br>without duplex unit  |
| Weight                          | 60.8 lbs. (27.6 kg) approx. (without Duplex unit)  |
| Power supply                    | 120 V ac<br>220 to 240 V ac @ 50/60 Hz $\pm$ 2%  |
| Power consumption               | Operating: 1200 W max.; 600 W average (77°F / 25°C)<br>Stand-by: 100 W average (77 °F / 25 °C)<br>Power saving: 15 W max.<br>Sleep: approx. 1 W (77 °F / 25 °C)  |
| Operating environment           | Operating: 50 to 89.6 °F (10 to 32 °C)/20 to 80% RH<br>[optimum 77 °F (25 °C) wet, 35.6 °F (2 °C) dry]<br>Off: 32 to 109.4°F (0 to 43 °C)/10 to 90% RH<br>[optimum 80°F (26.8 °C) wet, 35.6°F (2 °C) dry]                          |
| Print environment               | Mono Printing:<br>30 to 73% RH @ 50 °F (10 °C)<br>30 to 54% RH @ 89.6 °F (32 °C)<br>50 to 89.6 °F (10 to 32 °C) @ 30% RH<br>50 to 80.6 °F (10 to 27 °C) @ 80% RH<br>Color Printing:<br>62.6 to 80.6 °F (17 to 27 °C) @ 50 to 0% RH |
| Noise<br>(Sound pressure level) | Operating: 54 dB(A)<br>Standby: 37dB(A)  |

© 2013 Neopost USA Inc. All rights reserved.

No part of this document may be reproduced or distributed in any form or by any means without the express written permission of an authorized representative of Neopost USA.

This document and all information contained herein are confidential and may only be disclosed as necessary to support customer use of the equipment.

Limitations of this Document: The information presented herein is subject to change.

Neopost USA Inc. ASSUMES NO LIABILITY WHATSOEVER FOR ANY LOSSES OR DAMAGES RESULTING FROM USE OF THIS INFORMATION.